

NB	NB	Series	Outside Diameter	Wall Thickness	Weight of Black and GI Pipes
MM	Inches	Class	MM	MM	KG / MTR
15	1/2"	L	21.4	2.00	0.95
		M	21.8	2.60	1.23
		H	21.8	3.20	1.46
20	3/4"	L	26.9	2.30	1.39
		M	27.3	2.60	1.58
		H	27.3	3.20	1.90
25	1"	L	33.8	2.60	2.00
		M	34.2	3.20	2.44
		H	34.2	4.00	2.97
32	1 1/4"	L	42.5	2.60	2.55
		M	42.9	3.20	3.13
		H	42.9	4.00	3.83
40	1 1/2"	L	48.4	2.90	3.25
		M	48.8	3.20	3.59
		H	48.8	4.00	4.41
50	2"	L	60.2	2.90	4.09
		M	60.8	3.60	5.07
		H	60.8	4.50	6.23
65	2 1/2"	L	76.0	3.20	5.73
		M	76.6	3.60	6.46
		H	76.6	4.50	7.98
80	3"	L	88.7	3.20	6.73
		M	89.5	4.00	8.41
		H	89.5	4.80	10.00
100	4"	L	113.9	3.60	9.77
		M	115.0	4.50	12.23
		H	115.0	5.40	14.56
125	5"	M	140.8	4.80	16.06
		H	140.8	5.40	17.99
150	6"	M	166.5	4.80	19.09
		H	166.5	5.40	21.40

Tolerance (IS-1239 Pt-1)			
Wall Thickness	Light Series	-8%	+ Not Limited
	Medium & Heavy	-10%	+ Not Limited
Weight	Light Series	-8%	+10%
	Medium & Heavy	-10%	+10%